






ES-versa's standard cutting system allows to rough, beyel, polish, groove and safety bevels.



The multi-fluted cutter provides maximum versatility for specialty hevel profiles



Easy to use touch screen

## FFATURES + BENEFITS

Performance, productivity and popularity- the ES-versa provides the widest range of functionality, versatility and features of any table top edger in the industry. From the smallest to largest operations, the ES-Versa fulfills all your edging needs and is backed by the industry's most reliable service and support team.

- High-Wrap and Complex Beveling: High base lenses and complex shapes are handled proficiently with ES-versa's unique cutter design. Standard cutting system cover: rough, finish, polish, groove, and safety bevels. "Switch on the fly" to the multi-fluted cutter, which provides four different bevel geometries and can be configured with a wide variety of specialty blades.
- Precise Drilling: Control profits and performance with the cost effective, versatile drilling option. Retrieve thousands of pre-programmed drill data from manufacturers' specifications or easily input new ones.
- Small B Edging: As a standard, ES-versa allows processing B measurements as low as 18 mm; the optional small B package expands B capabilities down to 16 mm while maintaining the ability to edge a full range of lenses.
- Advanced Clamping: The electric clamping system minimizes slippage and crazing with controlled clamping
- Environmentally Friendly: Dry-cut technology eliminates water consumption and environmentally harsh coolants without sacrificing product quality.
- On-screen Assist: Real-time process control. Integrated, intelligent software provides directional assistance for the operator. Access on-screen operations, maintenance and parts manuals with the touch of a button.

### OPTIONS + ADDITIONAL FFATURES

#### Additional features:

- Comes complete with vacuum system and accessory kit
- One year parts and labor warranty
- Installation and training included

#### **Options:**

- Multi-fluted cutter
- Specialty cutters
- Barcode reader
- PCD cutter

# TECHNICAL INFORMATION

Weight	61 kg/ 135 lbs
Power	115 VAC 60Hz, 1500 W dedicated circuit; 230 VAC 50Hz, 1500W dedicated circuit
Working Range	<ul> <li>Maximum lens blank size: 100mm (effective diameter)</li> <li>Minimum finishing B size with (standard) half eye clamping assembly:18mm rimless; 20 mm bevel</li> <li>Minimum finishing B size with optional reduced clamping assembly: 16mm rimless; 18mm bevel</li> </ul>
Communications	OMA/VCA compatible

Stand alone

**Dimensions (wxdxh)** 64.3 x 67.5 x 72 cm / 25.3 x 26.6 x 28.4"

### **CONTACT**

Satisloh AG Neuhofstrasse 12 CH- 6340 Baar Switzerland Phone: +41 (0) 41766 16 16 Fax: +41 (0) 41766 16 10

Mail: info@satisloh.com

North America

Europe

Middle & South America Phone:

Email:

Phone:

Fmail:

Phone:

Phone:

Email:

+1 262 255 6001 info.usa@satisloh.com +49 (0) 6441 912 0 info.de@satisloh.com +852 27 56 7711 info.asia@satisloh.com +55 (24) 2233 8600 info.latam@satisloh.com

+1 262 255 6001 service.usa@satisloh.com +49 (0) 6441 912 222 service.de@satisloh.com +852 27 56 7654 service.asia@satisloh.com +55 (24) 2233 8686

servicio.latam@satisloh.com

